

軸径 D_p (mm)	肉厚 t (mm)	単位重量 (kg/m)	短期許容トルク (kN・m)	長期許容圧縮力 ※腐食しろ1mm考慮 (kN)
89.1	3.5	7.39	7.2	135
101.6	3.4	8.23	9.3	145
114.3	3.7	10.10	12.9	184
139.8	3.7	12.40	19.6	222
139.8	4.5	15.00	23.5	295
139.8	6.6	21.70	32.9	503
165.2	4.0	15.90	29.9	290
165.2	5.0	19.80	36.7	398
165.2	7.1	27.70	50.1	642
190.7	5.3	24.20	52.2	491
190.7	7.0	31.70	67.1	714
190.7	8.2	36.90	77.1	878
216.3	5.8	30.10	73.7	623
216.3	8.2	42.10	100.8	980
216.3	10.3	52.30	123.0	1297
216.3	12.7	63.80	146.6	1613
267.4	6.6	42.50	129.1	895
267.4	8.0	51.20	154.0	1144
267.4	9.3	59.20	176.4	1385
267.4	12.7	79.80	231.8	2020
318.5	8.0	61.30	221.7	1338
318.5	10.3	78.30	279.3	1836
318.5	12.7	95.80	336.6	2382
318.5	14.3	107.00	373.3	2744
355.6	9.5	81.10	326.4	1830
355.6	12.7	107.00	424.7	2622
355.6	14.3	120.00	472.0	3033
355.6	16.0	134.00	520.5	3457
※ 406.4	9.5	93.00	431.0	2065
※ 406.4	12.7	123.00	562.6	2944
※ 406.4	16.0	154.00	691.6	3902
※ 406.4	19.0	182.00	803.0	4734

※受注生産